



X40 Data Sheet

There is nothing usual about the X-Range, and the X40 is just the beginning. Our first drainage inspection camera system to come with multiple control & surveying options. You can use:

- 1) your own mobile phone/tablet (IOS or Android)
 - i) with a free looksee app (mina) you can download, or
 - ii) a reporting app with a monthly subscription
- 2) a bespoke tablet with full mina & WinCan ProTouch
- 3) a Scanprobe control box with full mina & WinCan embedded capabilities

The X40 rod and camera are designed to be flexible enough to passthrough trap bends but rigid enough to push the distance in abrasive pipes.

Rod Length	40 metres
Rod Diameter	8.0mm
Coiler Weight	12.0 kg
Coiler Dimensions	W 296cm, H 483cm, L 392cm
Camera Diameter	30mm
Pipe Use	50mm to 150mm Ø
Sonde/Beacon	33kHz or 512Hz (optional)
Meterage Counter	Yes
Self-levelling camera	Yes
Camera Resolution	PAL: 720Hx576V
Light Source	12 LED
Operating Temperature	-10°C - +50°C
Output	USB-C
Battery type	Li-ion
Battery Life	Up to 6 hours
Capacity	6.52Ah
Charge Current	1.5A
Nominal Voltage	7.4V
IP Rating	Camera: IP68, Coiler: IP54
Approvals	CE and UKCA



SCAN FOR MORE INFO



Premium Pipe Relining Materials and Equipment
SALES • SERVICE • HIRE

☎ 1800 747 326
 ✉ orders@pipecore.com.au
 🌐 pipecore.com.au