



PICOTE TWISTER FAMILY

Reinstatement & Cleaning



Twister Mini Flexi

Extremely agile Twister that makes difficult reinstatements through p-traps accessible.

Sizes: DN50 & 70/75 (2 & 3")
Shaft Size: 8mm (1/3")
Use with Mini Cleaner



Twister Express

Our most efficient reinstatement Twister. Great for multiple reinstatements per day.

Sizes: DN50 & 75 (2 & 3")
Shaft Size: 8mm (1/3")
Sizes: DN70 & 100 (3 & 4")
Versions: lined & unlined
Shaft Size: 12mm (1/2")



Twister Standard

Designed for connection reinstatements and is highly versatile and consistent.

Sizes: DN100, 150, & 200 (4, 6, & 8")
Versions: lined & unlined
Shaft Size: 12mm (1/2")



Tiger Twister

Reinstate connections quickly, even with fiberglass liners & UV resins, creating an impressive initial opening. Features the 6mm Tiger Front Metal Panel and Front Drill Head with the extra-hard Tiger Carbides.

Sizes: DN100, 125, 150, & 200
(4, 5, 6 & 8")
Versions: lined & unlined
Shaft Size: 12mm (1/2")



Twister Power+

Designed for the Maxi Power+ and working in larger pipes for reinstatements and cleaning.

Sizes: DN150, 200, 225, 250, & 300
(6, 8, 9, 10, & 12")
Shaft Size: 18mm (3/4")
Use with Maxi Power+



Twister Cleaner

Designed for light cleaning and working in plastic & fragile pitch fiber & Orangeburg pipe.

Sizes: DN100 (4")
Shaft Size: 12mm (1/2")

*See the other side for the
Liner, Concrete, & Metal Removers.*

PICOTE TWISTER FAMILY

Liner, Concrete & Metal Removers



Twister Liner Remover

Designed to remove failed linings. 3mm thick front metal panel, dual front brushes, and aggressive carbide help make short work of lining removal.

Sizes: DN100 & 150 (4 & 6")
Versions: lined & unlined
Shaft Size: 12mm (1/2")



Twister Concrete Remover

Dual front brushes provide stability, heavy duty front panel with large carbides and specialized front drill head combine for efficient concrete, grout, slurry, & rock removal.

Sizes: DN100 & 150 (4 & 6")
Shaft Size: 12mm (1/2")
Sizes: DN150, 200, 225 (6, 8 & 9")
Shaft Size: 18mm (3/4")



Twister Metal Grinder

Quickly and efficiently grinds away most metal including rebar, steel rods, nails, screws, and lead joints without damaging the host pipe.

Sizes: DN100 (4")
Shaft Size: 12mm (1/2")



Tiger Twister Liner & Concrete Remover

Two tough jobs, one tougher tool. Removed failed CIPP lining twice as fast than with a regular Twister Liner Remover as well as removing concrete. 3mm thick front Tiger metal panel, dual front brushes, and aggressive carbide help make short work of lining removal

Sizes: DN100 & 150 (4 & 6")
Versions: lined & unlined
Shaft Size: 12mm (1/2")



Smart Crusher

Recommended for the toughest lining removal projects. The Smart Crusher's extra strong front stabilizing brushes and shaft design make it extremely reliable for working in difficult lining removal applications. 2 Heads available: Flat Crusher Head for collapses positioned in the center or fully collapsed to the bottom or Drill Heads for failed linings where the top has sagged.

Sizes: DN70, 100, 150, 200 & 225 (3, 4, 6, 8 & 9")
Shaft Size: 18mm (3/4")
Use with Maxi Power+

See the other side for the Reinstatement & Cleaning Twisters