

PIPE CORE SUPERFLEX LINER

JULY 2021 | VERSION 1.1

PRODUCT DESCRIPTION

Flexible polyester knitted hose with polyurethane coating, available from DN 40 to DN 150.

Designed, tested and manufactured by I.S.T. Germany, SuperFlex Liner is flexible and versatile.



For more information please visit our website at pipcore.com.au

CERTIFICATION

WaterMark License

Pipe Core Superflex Liner is designed and tested in accordance with ISO 11294.4. When cured with the I.S.T. EasyPox epoxy resin, certified by DIBt Z-42.3-414 as a CIPP system, Superflex Liner complies with our WaterMark License No. 23295.



The parameters of ISO 11294.4 requires the system of a cured liner to be tested to a ***minimum service life of 50 years.***

Pipe Core Superflex Liner is compliant with WMTS-518:2017 Rehabilitation of existing Non Pressure Pipelines for the end use as Cured In Place Pipe (CIPP).



TECHNICAL DATA

Delivery Status	Material Data	ISO Test Method
Weight	approx. 750g/m ²	DIN EN 29073 T1
Thickness With Coating	approx. 3.0mm	DIN EN 29073 T2
Pore Volume	approx. 85%	
Fibres	polyester	
Coating	Polyurethane PU	
Coating Thickness	approx. 250µm	
Seam Type	Stitched	
Curing	Ambient, Hot Water, Steam Mix	
Properties	For bends up to 90° max. Max. 1 diameter changes eg 100>125mm	



Premium Pipe Relining Materials and Equipment
SALES • SERVICE • HIRE

☎ 1800 747 326
✉ orders@pipecore.com.au
🌐 pipecore.com.au